



### T-PULL HANDLE - BLK, GN

Product codes: 7025 | 7026 | 7027 | 7028 | 7054 | 7055 | 7063 | 7064 | 7065 | 7066 | 7069 | 7070  
7092 | 7093 | 7094 | 7095 | 7096 | 7097 | 7103 | 7104 | 7119 | 7120 | 7121 | 7122  
7123 | 7124 | 7125 | 7126 | 7127 | 7134 | 7159 | 7160 | 7161 | 7162 | 7163 | 7164


#### BACK TO BACK FIXING



1. Mark the fixing position on the door. Ensure adequate space is provided for clearance of knuckles on the door jamb.




2. Drill 10mm diameter holes for the through bolts.  
*Note: For glass doors a 12mm diameter hole may be required if rubber sleeves are used.*




3. Mount the outside handle by bolting through the door. Include the mounting base for the inside handle.

*Note: Only use rubber sleeves and washers for glass doors.*




4. Fix the inside handle over the brass bush and fasten with the grubscrews.


#### SINGLE HANDLE REAR FIX



1. Mark the fixing position on the door. Ensure adequate space is provided for clearance of knuckles on the door jamb.




2. Drill 10mm holes for the through bolts.




3. Mount the handle by bolting through the door.


#### SINGLE HANDLE FACE FIX



1. Mark the fixing position on the door. Ensure adequate space is provided for clearance of knuckles on the door jamb.



2. Drill 10mm diameter holes and screw the mounting bases to the face of door using the large screws supplied.



3. Fix the handle over the brass bush and fasten with the grubscrews.

*Note: Face fixing is not recommended on Cedar or other soft timber doors.*

**T-PULL HANDLE  
- BLK, GN**

Product codes:	7025	7026	7027	7028	7054	7055	7063	7064	7065	7066	7069	7070
	7092	7093	7094	7095	7096	7097	7103	7104	7119	7120	7121	7122
	7123	7124	7125	7126	7127	7134	7159	7160	7161	7162	7163	7164

## CARE & MAINTENANCE INSTRUCTIONS

It is recommended that all painting or staining of the doors is completed prior to installation of the door handles.

### MATT BLACK/GRAPHITE NICKEL

To protect your handles we suggest cleaning the surface of your hardware periodically with a warm soapy lightly dampened cloth to remove any build-up of dust and grime that may cause corrosion and affect the integrity of the finish. Then simply dry thoroughly with a clean, soft cloth. Minimum of monthly cleaning of door handles is recommended for both finish preservation and general hygiene.

Atmospheric conditions, salt deposits, acids, caustic agents, cement or dust on construction sites all have the potential to cause discolouration to the surface.

Please avoid using any metal polishes, abrasive cleaners, scorers or rough cloths that may damage or scratch the hardware and do not spray or immerse the hardware in liquid to clean.