



D-PULL HANDLE - BLK, GN

Product codes: 7098 | 7099 | 7100 | 7101 | 7102 | 7128 | 7129 | 7130 | 7131 | 7181
7182 | 7183 | 7187 | 7188 | 7189 | 7190 | 7238 | 7239 | 7240 | 7241

BACK TO BACK FIXING




1. Mark the fixing position on the door. Ensure adequate space is provided for clearance of knuckles on the door jamb.




3. Mount the outside handle by bolting through the door. Include the mounting base for the inside handle.

Note: Only use rubber sleeves and washers for glass doors.




2. Drill 10mm diameter holes for the through bolts.

Note: For glass doors a 12mm diameter hole may be required if rubber sleeves are used.




4. Fix the inside handle over the brass bush and fasten with the grubscrews.


SINGLE HANDLE REAR FIX



1. Mark the fixing position on the door. Ensure adequate space is provided for clearance of knuckles on the door jamb.




3. Mount the handle by bolting through the door.




2. Drill 10mm holes for the through bolts.


SINGLE HANDLE FACE FIX



1. Mark the fixing position on the door. Ensure adequate space is provided for clearance of knuckles on the door jamb.



3. Fix the handle over the brass bush and fasten with the grubscrews.



2. Drill 10mm diameter holes and screw the mounting bases to the face of door using the large screws supplied.

Note: Face fixing is not recommended on Cedar or other soft timber doors.

D-PULL HANDLE - BLK, GN

Product codes: 7098 | 7099 | 7100 | 7101 | 7102 | 7128 | 7129 | 7130 | 7131 | 7181
7182 | 7183 | 7187 | 7188 | 7189 | 7190 | 7238 | 7239 | 7240 | 7241

CARE & MAINTENANCE INSTRUCTIONS

It is recommended that all painting or staining of the doors is completed prior to installation of the door handles.

MATT BLACK/GRAPHITE NICKEL

To protect your handles we suggest cleaning the surface of your hardware periodically with a warm soapy lightly dampened cloth to remove any build-up of dust and grime that may cause corrosion and affect the integrity of the finish. Then simply dry thoroughly with a clean, soft cloth. Minimum of monthly cleaning of door handles is recommended for both finish preservation and general hygiene.

Atmospheric conditions, salt deposits, acids, caustic agents, cement or dust on construction sites all have the potential to cause discolouration to the surface.

Please avoid using any metal polishes, abrasive cleaners, scorers or rough cloths that may damage or scratch the hardware and do not spray or immerse the hardware in liquid to clean.